

Product data sheet

Specifications



Manual Motor Switch, TeSys Vario, rotary handle, 20A, 3 pole, 10HP at 480V, metallic enclosure, UL Type 12

9421V1A30

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Color	Red/yellow
Enclosure type	Dust and damp proof enclosure indendørs
Lock type	Padlockable
Range of Product	VARIO

Complementary

Line Rated Current	20 A
Auxiliary contact composition	Uden
Depth	6.25 in (158.75 mm)
Device mounting	Surface
Enclosure material	metallic metal
Height	7.38 in (187.45 mm)
Maximum Horse Power Rating	5 hp 240 V AC 10 hp 480/600 V AC
Permissible voltage	600 V AC
Width	5.5 in (139.7 mm)

Environment

NEMA Degree of Protection	NEMA 12
Product Certifications	UL listed file E164864 CCN NLRV CSA LR81630 class 3211 05

Ordering and shipping details

Category	US10CP121730
Discount Schedule	0CP1
GTIN	785901058908
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	5.80 in (14.732 cm)
Package 1 Width	7.40 in (18.796 cm)
Package 1 Length	7.90 in (20.066 cm)
Package weight(Lbs)	3.860 lb(US) (1.751 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.